



BUSHPEX WATER & GAS BALL VALVE



- Made of Lead Free DR Brass
- elson BUSHPEX Ball Valve
 - WaterMark Certificate No: WMKA 21922. Conforms with AS 5830.1
 - BUSHPEX Ball Valve Allowable Operating Pressure (AOP): 2000kPa
- PRESS/BUSHPEX Conversion Ball Valve (AOP): 1600kPa
- Working Temperature: from -20 °C to 95°C
- elson BUSHPEX Gas Ball Valve
- AGA approved No: 8350. Conforms with AS 4617
- Allowable Operating Pressure (AOP): 500kPa
- Working Temperature: from -20°C to 95°C
- 1/4 Turn full-bore for optimum flow
- Every valve is pressure tested by Elson prior to release
- Manufactured by elson, certified to ISO 9001

WaterMark WaterMark WMKA 21922 Standard AS 5830.1 WMKA02497 Standard AS 3688 TM WaterMark AGA WMKA21276 Standard AS/NZS 2537.2





Version 2.0 Aug 2020

Australian Standard

38 Eddie Road, Minchinbury NSW 2770

Elson Australasia Pty Ltd Tel: (02)9625 7899

ABN 45 059 613 991 Fax: (02)9625 7855

Email: sales@elson.net.au

TAPWARE | BUSHPEX | BRASSWARE | PRESS www.elson.net.au j www.bushpex.com