


HOSE BARB MALE

Brand Name: **elson**



| CODE | DESCRIPTION | L(mm) | A |
|-------|-------------------------------|-------|--------|
| 88112 | 6m m MIx8mm (1/4"x1/4") HOSE | 37.4 | R1/4 |
| 88115 | 6m m MIx10mm (1/4"x3/8") HOSE | 37.9 | R1/4 |
| 88118 | 6m m MIx15mm (1/4"x1/2") HOSE | 41.4 | R1/4 |
| 88124 | 10m m MIx8mm (3/8"x1/4") HOSE | 38.8 | R3/8 |
| 88127 | 10m m MIx10m m HOSE | 38.3 | R3/8 |
| 88130 | 10m m MIx15m m HOSE | 41.8 | R3/8 |
| 88133 | 15m m MIx8mm (1/2"x1/4") HOSE | 42.1 | R1/2 |
| 88136 | 15m m MIx10m m HOSE | 42.6 | R1/2 |
| 88139 | 15m m MIx15m m HOSE | 46.1 | R1/2 |
| 88142 | 15m m MIx20m m HOSE | 44.6 | R1/2 |
| 88148 | 20m m MIx15m m HOSE | 47.4 | R3/4 |
| 88151 | 20m m MIx20m m HOSE | 51.4 | R3/4 |
| 88154 | 20m m MIx25m m HOSE | 53.4 | R3/4 |
| 88157 | 25m m MIx20m m HOSE | 53 | R1 |
| 88160 | 25m m MIx25m m HOSE | 56 | R1 |
| 88163 | 25m m MIx32m m HOSE | 68 | R1 |
| 88169 | 32m m MIx25m m HOSE | 60.3 | R1 1/4 |
| 88172 | 32m m MIx32m m HOSE | 72.3 | R1 1/4 |
| 88175 | 32m m MIx40m m HOSE | 72.3 | R1 1/4 |
| 88178 | 40m m MIx32m m HOSE | 73.3 | R1 1/2 |
| 88181 | 40m m MIx40m m HOSE | 73.3 | R1 1/2 |
| 88187 | 50m m MIx40m m HOSE | 77.6 | R2 |
| 88190 | 50m m MIx50m m HOSE | 77.6 | R2 |

Product Specification & Features

- Maximum Working Temperature: 95°C
- Maximum Working Pressure at 20°C : 2000Kpa
- Threads: Complies with AS ISO 7.1,AS ISO 7.2
- Material: DR Brass, Complies with AS 2345
- Suitable for Potable Water – complies with AS/NZS 4020

Elson Australasia Pty Ltd

Tel: 02 9625 7899 Fax: 02 9625 7855

Website:www.elson.net.au E-mail:sales@elson.net.au



Version 1.0

Nov. 2020